

# Coiled Tubing

## IN STAINLESS STEEL SEAMLESS AND WELDED EXECUTION.

According to ASTM A213 / A269 type 316/316L & 304/304L & 316Ti.

According to DIN 17458, DIN 17457, D4 / T3 and D3 / T3, DIN 2462 / DIN 2463.

Bright & annealed, hardness is max. 90

HRB, and /or acc. to NACE MR 01.75.

Eddy current and hydrostatic tested on request.



### On request

Alloy 321, 310/S, 904L, 400, 600, 825, C276, Titanium Gr.2, Duplex 31803 and Copper.

B68/B75. In bright finish or with 1.00 mm black PVC cover. Sizes : 6.00 mm up to 12.00 mm and 1/4" up to 1/2".

### Applications

Measuring, control and monitoring systems in the chemical and petrochemical industries, shipbuilding and offshore industries and paper industries, etc.

### Tube bundles

Available on request, produced from our stainless steel tubes : Pre-insulated single or assembled multiple tubing, with options for steam or electrical trace heating, providing a system for safe transmission and temperature control of gasses and liquids. Number of tubes available up to 12 core bundles.

### Copper tubes

Available on coils of 30, 50 and 300 meters long, according to Si-Cu, ASTM

## STANDARD DIMENSIONS

*available from stock*

Metrics Sizes		Imperial Sizes	
0.80 x 0.25 mm	8.00 x 1.00 mm	1/32" x 0.007"	3/8" x 0.048"
2.00 x 0.95 mm	10.00 x 1.00 mm	1/16" x 0.010"	3/8" x 0.065"
2.50 x 1.15 mm	10.00 x 1.50 mm	1/16" x 0.014"	1/2" x 0.035"
2.50 x 1.21 mm	12.00 x 1.00 mm	1/16" x 0.020"	1/2" x 0.048"
3.00 x 0.50 mm	12.00 x 1.50 mm	1/8" x 0.020"	1/2" x 0.065"
3.00 x 1.00 mm	14.00 x 1.00 mm	1/8" x 0.028"	3/4" x 0.035"
4.00 x 0.50 mm	15.00 x 1.00 mm	3/16" x 0.035"	3/4" x 0.048"
4.00 x 1.00 mm	16.00 x 1.00 mm	1/4" x 0.035"	3/4" x 0.065"
5.00 x 1.00 mm	18.00 x 1.50 mm	1/4" x 0.048"	1" x 0.048"
6.00 x 0.50 mm	20.00 x 1.50 mm	1/4" x 0.065"	1" x 0.065"
6.00 x 1.00 mm		3/8" x 0.035"	

\* The coil lengths are between 30 till 400 meters.

\* The inside coil diameter is by 5.00 mm and smaller between 200 till 400 mm.

\* The inside coil diameter is by 6.00 mm and above between 400 till 680 mm.

\* On request we can connect the coils with an orbital weld, up to 10.000 mtr. long.

\* All tubes are "standard industrial clean".

\* Packing : as loose coil in carton boxes or on wooden drums.